



Material Safety Data Sheet

Health Emergency Phone Number: (217-222-5400)

Section I - Product Identification

Trade Name and Synonyms
ChampLub

Part Numbers:
P08907A, P08908A, P08909A, P09479A

Manufacturer's Name
Champion Pneumatic

Address
1301 North Euclid Ave., Princeton, IL 61356

Product Identification
Hydrocarbon Reciprocating Compressor Oil

Chemical Names and Synonyms
Petroleum Hydrocarbon

H.M.I.S.

Health: 1
Flammability: 1
Reactivity: 0
These ratings should be used only as a part of a fully implemented H.M.I.S. program.

Section II - Typical Chemical and Physical Properties

Appearance:	Amber to light Liquid	% Vol by Vol:	Nil
Boiling Point:	>300°F	Soluble in Water:	Negligibly
Melting Point:	ND	Vapor Density:	> Air
Specific Gravity:	0.88 (approx.)	Evaporation Rate:	NA

** Vapor Density of Air is = 1 **

** Evaporation Rate of Butyl Acetate is = 1 **

Section III - Composition/Information of Ingredients

Composition	Case #	%	PEL
P: Industrial Oil	Mixture	100	5 mg/CUM
1: Solv. Ref. Hvy. Paraffin Oil	64742-54-7		6 mg/CUM
2: Lt. Naph. Hydrotreated Dist.	64742-53-6		7 mg/CUM
3: Hvy. Naph. Hydrotreated Dist.	64742-67-7		8 mg/CUM
4: Deasphalted Residium	64742-95-3		9 mg/CUM
5: Solv. Ref. Sat. Paraffin Dist.	64742-65-0		10 mg/CUM (as mist)

Section IV - HMIS Hazard Rating

Least	0	Health	1
Slight	1	Fire	1
Moderate	2	Reactivity	0
High	3	Other	0
Extreme	4	Personal Protection	B

Section V - Hazards Identification

Acute Health	No	Reactivity	No
Chronic Health	No	Fire	No

Section VI - Emergency and First Aid Procedures

Eye Contact:	As with most foreign materials, if eye contact should occur, flush eyes with plenty of water. If irritation occurs, get medical attention.
Skin Contact:	Wash exposed skin with soap and water. Remove contaminated clothing and wash before reuse.
Inhalation:	Remove exposed person to fresh air if adverse effects are observed.
Ingestion:	DO NOT INDUCE VOMITING. Get medical attention.